



IT45



Model	IT45
Product Type	Zoom Bullet
Maximum Resolution	2MP
Application Environment	Outdoor
Image Sensor	Progressive Scan CMOS
Day / Night	Yes
Low Light Sensitivity	Extreme
Minimum Illumination	Color: 0.1 lux, B/W: 0 lux (IR LED on) at F1.6
Mechanical IR Cut Filter	Yes
IR LED	Adaptive IR LED
IR Working Distance	40m
Lens	Zoom, f4.3-129mm / F1.6-5.0, DC iris, Auto focus
Zoom Ratio	30x optical
Zoom Application	Camera Installation; Auto Zoom by Event; Manual Operation
Lens Mount	Board mount
Horizontal Viewing Angle	65.6°-2.07°
Compression	H.264 (Baseline/ Main/ High profile), MJPEG
Maximum Frame Rate vs. Resolution	30 fps at 1920 x 1080 30 fps at 1280 x 720 30 fps at 800 x 600 30 fps at 640 x 480 15 fps at 320 x 240
Horizontal Resolution (TV lines)	1800 TVL
Multi-Streaming	Dual streams
Video Motion Detection	3 regions
Privacy Mask	32 configurable regions
Wide Dynamic Range	Extreme WDR (145 dB)
Digital Noise Reduction	2D+3D DNR
Digital Image Stabilizer	Digital Image Stabilizer (available with camera firmware v6.08 or newer)
Defogging	Defogging
S/N Ratio	56 dB
Audio	2-way (Line-in, Line-out)

Network Protocol & Service	TCP, UDP, HTTP, HTTPS, DHCP, PPPoE, RTP, RTSP, IPv6, DNS, DDNS, NTP, ICMP, ARP, IGMP, SMTP, FTP, UPnP, SNMP, Bonjour, Pelco-D
Pan, Tilt or Zoom protocol	Visca, Pelco-D, Pelco-P
Network Connector	RJ-45
Digital Input/Output	1/1
Local Storage	MicroSDHC/MicroSDXC memory card slot (card not included)
Power Source	DC 12V; PoE Class 3
Environmental Casing	Weatherproof (IP67); Vandal proof metal casing (IK10)
Bundled Accessories	Integrated Bracket
Mount Type	Wall, Ceiling, Pole, Gang Box
Software Based Analytics (require PC based Smart Search Tool, IVS Server or ALPR Server)	Face Detection, Motion Detection, Tamper, People Counting, Line crossing, Enter area, Exit area, Appear in area, Missing object, Unattended object, Crowd detection, Forbidden direction, Vehicle Counting, Heat Map, License Plate Recognition, Speed Detection
GPS Position	Manual setting
Client PC Operating System	Windows 8, Windows 7, Windows Server 2008, Windows Vista, Windows Server 2003, Windows XP
PC Web Browser	IE 8, IE 9, IE 10, IE 11, Firefox with VLC, Chrome with VLC, Safari with Quicktime
ONVIF Compliant	Yes (Profile S, Profile G available on new firmware v6.09)
Packing Dimension (L x W x H)	37 x 27.2 x 18.3 (cm)
Heater	Yes
Fan	No
Starting Temperature	-40°C ~ 50°C (-40°F ~ 122°F) within 30 minutes
Operating Temperature	-40°C ~ 50°C (-40°F ~ 122°F)
Approvals	CE, FCC, IP67, NEMA 4X, IK10 (metal casing), UL (for optional PoE injector and power adapter)
Warranty	3 Years
Product Availability	ACTi : Now Distributor : Now
Customer Price	USD\$1,638