

Privacy Mask	Up to 17 preset points including home position with up to 4 configurable regions for each position
AGC Control	Selectable
Wide Dynamic Range	Superior D-WDR (110 dB)
Digital Noise Reduction	3D-DNR
S/N Ratio	52 dB
Audio	2-way (Line-in, Line-out)
Audio Compression s configurable	AAC LC 8/16 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz
Network Storage	NAS (Support NFS SMB/CIFS),FTP
Network Protocol & Service	TCP/IP, UDP, HTTP, HTTPS, DHCP, PPPoE, RTP, RTSP, RTCP, IPv6, DNS, DDNS, NTP, ICMP, ARP, IGMP, SMTP, FTP, UPnP, SNMP, IGMP, Bonjour, Pelco-D, 802.1X, QoS, Zeroconf, AR, Bonjour,...
Pan, Tilt or Zoom protocol	Visca, Pelco-D, Pelco-P
White balance	Automatic ,Manual
Ethernet Interface / Network Connector	RJ-45 10/100, BASE-T
Digital Input/Output	1/1
Audio Input/Output	Line-in, Line-out, Built-in Microphone
Audio Streaming	Two-Way
Audio compression Configurable	*AAC LC 8/16 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz *Configurable bit rate *AAC LC 8/16 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz
Audio formats supported	PCM
Local Storage	MicroSDHC/MicroSDXC memory card slot (64GB Included)
Power Source	DC 12V/24V AC; PoE Class 3, 802.3af
Environmental Casing, (Outdoor Rating)	Weatherproof (IP67) Rated
Vandal Resisit	Vandal Proof Metal Casing (IK10) Rated
Mounting Bracket	Integrated Bracket
Mount Type	Wall, Ceiling, Pole, Gang Box
Software Based Analytics (require PC based Smart Search Tool, IVS Server or ALPR Server)	Face Detection, Motion Detection, Tamper, People Counting, Line crossing, Enter area, Exit area, Appear in area, Missing object, Unattended object, Crowd detection, Forbidden direction, Vehicle Counting, Heat Map, License Plate Recognition, Speed Detection
GPS Position	Manual setting

Client PC Operating System	Windows 8, Windows 7, Windows Server 2008, Windows Vista, Windows Server 2003, Windows XP
PC Web Browser	IE 8, IE 9, IE 10, IE 11, Firefox with VLC, Chrome with VLC, Safari with Quicktime
ONVIF Compliant	Yes (Profile S, Profile G)
Packing Dimension (L x W x H)	37 x 27.2 x 18.3 (cm)
Heater	Yes
Starting Temperature	-40°C ~ 50°C (-40°F ~ 122°F) within 30 minutes
Operating Temperature	-40°C ~ 50°C (-40°F ~ 122°F)
Approvals	CE, FCC, IP67, NEMA 4X, IK10 (metal casing), UL (for optional PoE injector and power adapter)
IP address filtering	Yes
Infra-red wavelength	850 nm
Power consumption (PoE)	30W
Power consumption (typical)	5W
Password protection type	User
Web-based management	Yes
Reset button	Yes
Video Protection	Watermark
Weight	0.750 kg
Body	Metal
Camera Support License	2 Years Corporate Camera Support License
Warranty	2 Years
Product Origin	UK

