



	ETNR-180P
	
Model	ETNR-180P
Product Type	Standalone NVR
Maximum Number of Video devices	32
Maximum Number of Clients	1 local, 128 remote
License required	No
Free License	16
Video Resolution	Support all cameras resolutions up 10 MP
Compression	H.264, MPEG-4, MJPEG
Processor	Dual Core
RAM	8 GB
Audio	2-way
Network Interface	1 X RJ45, 10/100/1000Mbps Self - adaptive Interface
Built-in PoE Connectors	16 Ports
Wireless Specifications	IEEE 802.11n/g/b/a, Wi-Fi, 4G, GPS (need optional accessories)
Digital Input/Output	2/2
Serial Port	RS-232
Power Source	AC 110-240V
PoE Output	Per Port Max. 15.4 watts
PoE Power Budget	Max. 240 watts
Built-in Analytics	Shock Detection with built-in G-sensor
Scheduled Recording	Yes
Event Recording	Yes
Manual Recording	Yes
Speed Up	Yes
Dual Stream Management	Yes
Incoming Bandwidth	100Mbps
Outgoing Bandwidth	240Mbps
HDD Interface	Maximum 24TB or 4 SATA disks (4*6TB)
Hard Disk Included	24TB HDD is Included, (4*6TB)
External Storage Interface	eSATA, iSCSI, USB
Display Layout Mode	TBD

Local Display Performance	Standalone NVR
Digital Zoom	Yes
Event Status	Display event status upon alarm or upon connection loss or recovery between server and client
Instant Playback	Instant Playback in live view window (Remote client)
PTZ Control	Yes
Playback Control	Continuous forward and backward playback with speeds 0.5x/1x/2x/4x/8x/16x/32x; pause; stop
Synchronized Playback	TBD
Local Access	HDMI/VGA monitor, USB keyboard & mouse
Remote Access	Web Client (IE), Mobile Client (iOS & Android)
Event Trigger	Video motion detection; External device through digital input; Network loss and recovery
Event Response	Record video; Beep; Digital output; E-mail with snapshots; Event logging; Go to PTZ preset point
Permission Control	Unlimited number of users, Customizable permissions for user groups
Video Export	eSATA, USB
Server Operating System	Embedded Linux
Client PC Operating System	Windows 8, Windows 7
PC Web Browser	IE 9, IE 10, IE 11
Unified Solution	Fully compatible with ONVIF cameras, encoders, central management system, TV wall and intelligent video surveillance software
Remote Configuration	YES*
ONVIF Compliant	Yes (Profile S)
Packing Dimension (L x W x H)	71.3 x 59.9 x 19.4 (cm)
Fan	Yes
Operating Temperature	0°C ~ 40°C (32°F ~ 104°F)
Approvals	CE, FCC, EN50155, UL (for built-in power adapter)
Chassis	Rack-mounted
Rack Space	1U
Connectable to the third-party network cameras	Yes

Up to 32 network cameras can be connected.	Yes, (NO Software Required)
Support live view, storage, and playback of the connected camera at up to 12 megapixels resolution	Yes
Compatible with third party devices	Yes
Warranty	2 Years
Product ORIGIN	UK