

iTM-IIB SERIES



Features:

- ◆ Metal IR Dome WIFI IP Camera
- ◆ IR LED: $\varnothing$ 5 X 24 pcs, IR Range: 50M
- ◆ Lens: 2.8mm(2M Pixels)
- ◆ Video Output: WIFI port
- ◆ Supports Onvif 2.0
- ◆ PNP(Plug and Play), support smart phone & tablets
- ◆ OSD, Motion Detection, Remote View and Control, IR-Cut
- ◆ Working Temperature: -10°C~ +60°C
- ◆ Size: 105×80 mm
- ◆ Weight: 480g



Specifications:

Model	iTM-IIB10	iTM-IIB13	iTM-IIB20
Image Sensor	1/4" 1.0 Megapixel CMOS	1/3" 1.3 Megapixel CMOS	1/2.5" 2.0 Megapixel CMOS
Resolution	1280×720	1280×960	1920×1080
Minimum Illumination	3300mV/Lux-sec	5500mV/Lux-sec	1.76V/Lux-sec
S/N Ratio	39db	44db	38.5db
Frame Rate	1.0 Megapixel @ 25FPS	1.3 Megapixel @ 25FPS	2.0 Megapixel @ 25FPS
Focus Mode	fixed		
Day/Night	IR cut filter with auto switch, IR sensor.		
Video Output	analog video out(optional), CVBS supported, PAL/NTSC (configurable)		
Network	2.4GHZ 50m to 100m reach		
Delay	Within The LAN0.3S		
Video Compression	H.264 compression ,dual stream (0.1M-6Mbps adjustable)		
Protocol	Protocols: RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP		
Onvif	Support Onvif 2.0		
User Permission	Multi-user Classification Management		
Power/Current	DC 12V/1A		
Consumption	3.0W		
Lens	3.6mm CS Lens (2M Pixels Lens)		
IR Status	IR LED: $\varnothing$ 5 x 24pcs IR LED, IR range: 20M		
Dimension (mm)	105mm x 80mm		
Weight (g)	480g		
Temperature	-10°C~+60°C		
Humidity	0%-90%		