



Model	ITM-PT120T130	ITM-PT150S200
Camera		
Image Sensor	1/3" Aptina Low Illumination 1.3MP CMOS	1/2.7" OmniVision Low Illumination 2MP CMOS
Horizontal Resolution	720P	1080P
S/N Ratio	>58db	
PTZ		
Horizontal Rotation Speed	200°/s	
Horizontal Rotation Range	360°	
Tilt Rotation Speed	100°/s	
Tilt Rotation Range	90°	
Auto Flip	Horizontal 180°, Vertical 93°	
Ratio Speed	Support	
360° Scan	User programmable	
360° Scan Speed	01-64speed setting available	
A-B Scan	User programmable	
A-B Scan Speed	01-64speed setting available	
PWR on Action	Memory/Tour/360 scan/AB scan/Home/Nop	
Park Time	1-60mins setting available	
Dwell Preset	1-60s interval available	
Preset Points	220	
Go to Preset Speed	200°/s	
Guard Tours	3 groups	
Guard Points	Max.16 points, dwell time user selectable	
Auxiliary Interface		
Audio	2 ways	
Communication Protocol	Pelco-D, Pelco-P	
Baud Rate	1200/2400/4800/9600bps	
General		
Operating Temperature	Indoor: 0°~ +40° Outdoor: -40°~ +60°	
Operating Humidity	≤95% Non Condensing	
Heater & Blower	Auto temperature control	
Wide Dynamic Range	Basic Superior WDR 120dB	
Digital Noise Reduction	3D DNR	
Zoom	22x Optical Zoom and 10x Digital Zoom	
OnVif	Profile S and G Support	
Lens	f=3.9mm-85.5mm	
Auto Control IR LED	PWM	
Intelligent Systems	Auto-Track	
Power	DC12V/3A	
IR Illumination Distance	150M with IR-CUT	
Power Consumption	≤ 36W	
Lightning Protection	Transient voltage 6000V	
Dimension	28x32x20(cm)	
Environment	IP66	
Weight	3.4kgs	