

ITM Systems Ltd

ADDRESS: Broadway Court, Peterborough, Cambridgeshire, PE1 1 RP, United Kingdom
Tel: 0044173 3567259 Fax: 0044843 5241649

X-Ray Baggage Inspection Machine

Model: XT6550

Tunnel Size : 650 (W) ×500 (H) mm
Power Requirement: 220V AC ($\pm 10\%$) 50 ± 3 Hz
Power consumption: 1.0KW (Max)
Noise level: <58dB
Conveyor Speed: 0.22m/s
Conveyor Max Load: 170 kg
Wire Resolution: 40AWG
Spatial Resolution: 1.0mm Horizontal and Vertical
Steel Penetration: 40mm
Single inspection dosage: < 1.2 μ Gy
Leakage radiation: <0.1 μ Gy/h
Film Safety: Guarantee ISO1600 Film



X-Ray Generator Specifications

Tube Current: 0.4~1.2MA (adjustable)
Anode Voltage: 100~160KV (adjustable)
Cooling: Sealed oil bath with forced air
Duty Cycle: Rated for 100% Duty Cycle
Beam Direction: Upward
Beam Angle: 60°
Detector: L-shaped Array

Image Display

19" High Resolution LCD Monitor
Display Resolution: 1280*1024; 24 bit/pixel Color
Colour Contrast Sensitivity: 24 Visible Levels, 4096 Gray Level
Image storage: 100,000 pictures in real time (can be customized)
Zoom: 64 Times Enlarge, Whole screen continuous observation
Multi-Energy (M) colour material identification: Organic objects in orange color, inorganic objects in blue colour, mixture in green colour
Edge enhancement: Object contour edge is more distinct
Super image enhancement: Image detail is more distinct
High penetration display: Increase the contrast of bright area in image to make the area that is easy to penetrate appear more clearly

ITM Systems Ltd

ADDRESS: Broadway Court, Peterborough, Cambridgeshire, PE1 1RP, United Kingdom
Tel: 0044173 3567259 **Fax:** 0044843 5241649

Low penetration display: Increase the contrast of dark areas in image to make the area that is difficult to penetrate appear more clearly.

Brightening/dimming: Increase/Decrease brightness of image

Image recurrence: Display the previous twenty images and process any one of them

Image restoration: Restore image to initial status

Assist to detect drug and explosive powder

Special features:

Network interface: Capable of connecting to LAN, and support multi-terminal check for baggage at same time

Safety ray: Ray is transmitted under automatic control, avoiding the error

One-key shutdown control: Just rotate the key to shut down the machine; it is safe, easy and convenient

Eagle eye: Capable of expediently observe the magnifying area

Self-diagnosis function: Give message automatically if malfunctioning for prompt maintenance

Environment Specifications:

Operating temperature/humidity: 0°C ~ 45°C/20% ~ 95% (Non-condensing)

Storage temperature/humidity: -20°C ~ 60°C/20% ~ 95% (Non-condensing)